

APHS HYBRID (C FRAME)		APHS H 31110	APHS H 31150	APHS H 31190	APHS H 31240	APHS H 31320	APHS H 41150	APHS H 41190	APHS H 41240	APHS H 41320	APHS H 41440	APHS H 61240	APHS H 61320	APHS H 61440	APHS H 61600	
Capacity		kN	1100	1500	1900	2400	3200	1500	1900	2400	3200	4400	2400	3200	4400	6000
Oil Tank Volume		lt	70	110	110	110	110	110	110	110	140	110	110	140	140	140
Motor Output		kW	2x6	2x10	2x10	2x10	2x10	2x10	2x10	2x10	2x30	2x10	2x10	2x30	2x30	2x30
Speeds (mm/s)	Approach	200	200	200	150	130	200	200	150	130	150	150	130	150	140	140
	Working	10	10	10	8	7	10	10	8	7	10	8	7	10	10	10
	Return	200	200	200	150	130	200	200	150	130	150	150	130	150	140	140
Approx. Weight		ton	9	10,3	10,7	11,7	15,7	12,8	13,3	14,5	19	27	25,5	30,5	39,5	56
Bending Length		mm	3100	3100	3100	3100	3100	4100	4100	4100	4100	4100	6100	6100	6100	6100
Inside Frames		mm	2550	2550	2550	2550	2550	3550	3550	3550	3550	3550	5100	5100	5100	5100
Side Frame Width		mm	2150	2150	2150	2170	2250	2150	2150	2170	2250	2390	2255	2550	2170	2375
Overall Width (Front View)		mm	3950	3970	3970	3990	4010	4970	4970	4990	5010	5010	7100	7100	7140	7140
Bed Height		mm	880	880	880	880	1000	880	880	880	1000	1000	1100	1185	1100	1050
Machine Height		mm	2915	2965	2985	2990	3325	2965	2985	2990	3325	3550	3250	3705	3900	4260
Daylight Opening		mm	540	540	530	530	660	530	530	530	635	570	500	580	630	745
Stroke		mm	260	260	260	260	320	260	260	260	320	320	260	320	320	360
Table Width		mm	60	60	90	90	380	60	90	90	280	380	90	200	280	380
Throat Gap		mm	460	460	460	460	500	460	460	460	500	500	500	500	500	500
Adapter Height		mm	80	80	80	80	80	80	80	80	80	125	80	80	110	125