

APHS MILD HYBRID TYPES (C FRAME)		APHS MH 125060	APHS MH 21080	APHS MH 26110	APHS MH 31110	APHS MH 31150	APHS MH 31190	APHS MH 31240	APHS MH 31320	APHS MH 31440	APHS MH 41150	APHS MH 41190	APHS MH 41240	APHS MH 41320	APHS MH 41440	APHS MH 37150	APHS MH 37190	APHS MH 37240	APHS MH 37320	APHS MH 61240	APHS MH 61320	APHS MH 61440	APHS MH 61600
Capacity	kN	600	800	1100	1100	1500	1900	2400	3200	4400	1500	1900	2400	3200	4400	1500	1900	2400	3200	2400	3200	4400	6000
Oil Tank Volume	lt	70	120	120	120	170	170	200	200	350	170	170	200	200	350	170	170	200	200	200	200	350	400
Motor Output	kW	8,5	8,5	8,5	8,5	20,3	20,3	20,3	20,3	32,7	20,3	20,3	20,3	20,3	32,7	20,3	20,3	20,3	20,3	20,3	20,3	32,7	32,7
Speeds (mm/s)	Approach	150	180	190	190	190	170	120	100	110	190	170	120	100	110	190	170	120	100	120	100	110	100
	Working	10	10	10	10	10	10	8	7	10	10	10	8	7	10	10	10	8	7	8	7	10	8
	Return	150	180	190	190	190	170	120	100	100	190	170	120	100	100	190	170	120	100	120	100	100	90
Approx. Weight	ton	5	6,5	7,5	8,7	10	10,4	11,4	15,5	22,5	12,5	12,7	14	19	27	11	12	13	17	26	31	40	56
Bending Length	mm	1250	2100	2600	3100	3100	3100	3100	3100	3100	4100	4100	4100	4100	4100	3700	3700	3700	3700	6100	6100	6100	6100
Inside Frames	mm	1070	1600	2050	2550	2550	2550	2550	2550	2550	3550	3550	3550	3550	3550	3250	3250	3250	3250	5100	5100	5100	5100
Side Frame Width	mm	1855	1950	1950	1950	1950	1950	1950	2175	2060	1950	1950	1950	2175	2390	1935	1975	1975	1935	2255	2550	2170	2375
Overall Width (Front View)	mm	2310	2860	3310	3810	3850	3830	3850	3870	4050	4830	4830	4850	4870	4830	4530	4530	4550	4570	7000	7000	7040	7040
Bed Height	mm	850	880	880	880	880	880	880	1000	1000	880	880	880	1000	1000	880	880	880	980	1100	1185	1100	1050
Machine Height	mm	2610	2595	2905	2905	2905	2895	2895	3245	3575	2895	2895	2895	3200	3350	2895	2895	2895	3200	3090	3705	3775	4240
Daylight Opening	mm	530	530	540	540	540	530	530	660	700	530	530	530	635	705	530	530	530	635	500	580	630	745
Stroke	mm	260	260	260	260	260	260	260	320	320	260	260	260	320	320	260	260	260	320	260	320	320	360
Table Width	mm	60	60	60	60	60	90	90	380	495	60	90	90	280	380	60	90	90	280	90	200	280	380
Throat Gap	mm	460	460	460	460	460	460	460	500	500	460	460	460	500	500	460	460	460	500	500	500	500	500
Adapter Height	mm	80	80	80	80	80	80	80	80	125	80	80	80	80	125	80	80	80	80	80	80	110	125